



Linear Power Supplies

Model
RPS-1210UL
10 Amps

Design Features

- Short circuit and over voltage protection
- Output power rated at continuous service
- Binding post output terminals
- Precision regulation of output voltage
- Low peak-peak ripple
- External fuse access
- High surge capacity

Applications

- Cellular telephones
- Auto-sound display and mobile sound systems
- Testing of DC equipment and appliances
- Household and portable entertainment equipment
- Automobile accessories
- Security systems
- Toys and hobbies
- Cooler boxes



2 YEAR WARRANTY

MODEL NO.	RPS-1210UL
INPUT VOLTAGE RANGE	110 - 120 VAC, 60 Hz
OUTPUT VOLTAGE	13.8 VDC
OUTPUT CURRENT, CONTINUOUS	10 A
MAXIMUM SURGE	14 A
OUTPUT VOLTAGE STABILITY	+/- 0.05 V
FUSE RATING	3 A
PEAK TO PEAK RIPPLE	< 10 mV
COOLING	By fan
OPERATING TEMPERATURE	0°C to 40°C
PROTECTIONS	Short circuit, over voltage
ENCLOSURE	Heavy duty metal case
TERMINALS	Heavy duty metal cabinet
DIMENSIONS, MM (L x W x H)	249 x 236 x 127
DIMENSIONS, INCHES (L x W x H)	9.8 x 9.3 x 5
WEIGHT, KG	8
WEIGHT, LB	17.6

NOTE: Specifications are subject to change without notice